

Message elements	RTGS supported character sets													
<p>All Proprietary and/or Text elements, with exception of:</p> <p>Initiating Party, Debtor, Ultimate Debtor, Creditor, Ultimate Creditor, Originator, Related Remittance Information and Remittance</p>	<p>Use of FIN X-Character Set:</p> <p>abcdefghijklmnopqrstuvwxyz</p> <p>ABCDEFGHIJKLMNOPQRSTUVWXYZ</p> <p>0123456789</p> <p>!-?:().,;'+</p> <p>Space</p>													
<p>For Initiating Party, Debtor, Ultimate Debtor, Creditor, Ultimate Creditor, Originator, Related Remittance Information and Remittance</p>	<p>Use of FIN X-Character set (see above), plus !#\$%&*^_`{ }~ " ; <> @ [\ .</p> <p>Note: 5 characters need to be escaped:</p> <table border="1" data-bbox="569 748 1503 1166"> <thead> <tr> <th data-bbox="569 748 1037 818">Character</th> <th data-bbox="1043 748 1503 818">XML Escape Sequence</th> </tr> </thead> <tbody> <tr> <td data-bbox="569 823 1037 893">"</td> <td data-bbox="1043 823 1503 893">&quot;</td> </tr> <tr> <td data-bbox="569 898 1037 967">'</td> <td data-bbox="1043 898 1503 967">&apos;</td> </tr> <tr> <td data-bbox="569 972 1037 1042"><</td> <td data-bbox="1043 972 1503 1042">&lt;</td> </tr> <tr> <td data-bbox="569 1047 1037 1117">></td> <td data-bbox="1043 1047 1503 1117">&gt;</td> </tr> <tr> <td data-bbox="569 1122 1037 1166">&</td> <td data-bbox="1043 1122 1503 1166">&amp;</td> </tr> </tbody> </table>		Character	XML Escape Sequence	"	"	'	'	<	<	>	>	&	&
Character	XML Escape Sequence													
"	"													
'	'													
<	<													
>	>													
&	&													